

WHAT IS CLAIMED AND DESIRED TO BE SECURED BY LETTERS  
PATENT OF THE UNITED STATES IS:

1. A method of preparing a packet communication,  
5 comprising the steps of:

determining a modulation scheme for each data field of a  
set of data fields;

placing an indication of the determined modulation schemes  
in a super frame header;

10 modulating each of the data fields according to the  
determined modulation schemes; and

transmitting the super frame header and each of the  
modulated data fields.

15 2. The method according to Claim 1, wherein said  
indication is an index that identifies a set of at least one of  
a modulation format, symbol rate, and FEC scheme to be used on  
the data packets.

20 (3. The method according to Claim 2, further comprising the  
step of transmitting a list of indexes and corresponding  
modulation schemes prior to transmitting the super frame header  
and data packets.

4. The method according to Claim 1, wherein said modulation schemes are at least one of QPSK, QAM 16, and QAM 64.

5. The method according to Claim 1, wherein said step of transmitting comprises transmitting said header and data packets using OFDM.

6. A method of dynamic modulation in a communication system, comprising:

preparing a header that indicates a modulation scheme of at least one data packet;

modulating the data packets according to the modulation scheme; and

transmitting the header and data packets.

7. The method according to Claim 6, wherein the modulation scheme includes at least one of a modulation format, symbol rate, and FEC scheme to be used on the data packets.

8. The method according to Claim 7, wherein said modulation scheme is one of QPSK, QAM16, and QAM 64.

9. The method according to Claim 6, wherein said step of transmitting comprises transmitting said header and data packets using OFDM.

5      10. The method according to Claim 6, further comprising the steps of:

receiving a status message transmitted from a receiver; and  
selecting the modulation scheme based on the received  
status message.

11. The method according to Claim 10, wherein said status message includes CNR information describing a Carrier to Noise Ratio of transmissions previously received by the receiver.

12. The method according to Claim 10, wherein said status message includes error count information describing a number of errors detected in transmissions received by the receiver.

13. The method according to Claim 12, wherein said error count is a bit error rate detected in transmissions received by the receiver.

14. A method of receiving dynamically modulated data packets, comprising the steps of:

10  
20  
30  
40  
50  
60  
70  
80  
90  
100  
110  
120  
130  
140  
150  
160  
170  
180  
190  
200  
210  
220  
230  
240  
250  
260  
270  
280  
290  
300  
310  
320  
330  
340  
350  
360  
370  
380  
390  
400  
410  
420  
430  
440  
450  
460  
470  
480  
490  
500  
510  
520  
530  
540  
550  
560  
570  
580  
590  
600  
610  
620  
630  
640  
650  
660  
670  
680  
690  
700  
710  
720  
730  
740  
750  
760  
770  
780  
790  
800  
810  
820  
830  
840  
850  
860  
870  
880  
890  
900  
910  
920  
930  
940  
950  
960  
970  
980  
990

receiving header data containing a modulation scheme used to modulate at least one data packet;

receiving the data packets; and

demodulating the data packets according to the modulation scheme contained in the header data.

15. The method according to Claim 14, wherein the modulation scheme includes at least one of a modulation format, symbol rate, and FEC scheme to be used on the data packets.

16. The method according to Claim 15, wherein said modulation scheme is one of QPSK, QAM16, and QAM 64.

17. The method according to Claim 14, wherein said steps of receiving header data and receiving the data packets comprises receiving said header and data packets using OFDM.

18. The method according to Claim 14, further comprising the steps of:

preparing a status message indicating a quality of transmissions received; and

transmitting the status message.

19. The method according to Claim 18, wherein said status message includes error count information describing a number of errors detected in the transmissions received.

5 20. A method for dynamic downstream communication in a broadband wireless access system, comprising:

transmitting a first packet from a wireless hub to a wireless modem utilizing a first downstream modulation type of a plurality of downstream modulation types;

receiving the first packet at the wireless modem;


demodulating the first packet at the wireless modem according to the first downstream modulation type;

transmitting a second packet from the wireless hub to the wireless modem utilizing a second downstream modulation type of the plurality downstream modulation types that is different than the first downstream modulation type;

receiving the second packet at the wireless modem; and

demodulating the second packet at the wireless modem according to the second downstream modulation type.

20 21. The method of Claim 20, wherein the second packet is a next data packet transmitted from the wireless hub to the wireless modem after the first packet.



22. The method of Claim 20, further comprising

transmitting a third packet from the wireless hub to the wireless modem utilizing the first downstream modulation type of the plurality downstream modulation types, wherein the third packet is transmitted prior to transmission of the second packet;

receiving the third packet at the wireless modem; and demodulating the third packet at the wireless modem according to the first downstream modulation type.

23. The method of Claim 20, further comprising the steps of

identifying the first downstream modulation type by reading a portion of the first packet comprising an identity of the first downstream modulation type; and

identifying the second downstream modulation type by reading a portion of the second packet comprising an identity of the second downstream modulation type.

24. The method of Claim 20, further comprising

determining at the wireless modem a carrier to noise ratio of a carrier signal utilized to transmit the first packet;

transmitting the carrier to noise ratio of the carrier signal utilized to transmit the first packet from the wireless modem to the wireless hub; and

determining at the wireless hub the second modulation type based upon the carrier to noise ratio.

25. The method of Claim 24 further comprising transmitting an in-phase pilot signal as part of a data portion of the first packet and transmitting an in phase pilot signal as part of a data portion of the second packet, wherein the carrier frequency is determined by the wireless modem-by utilizing the in-phase pilot signal.

26. The method of Claim 20 further comprising transmitting a training packet from the wireless hub to the wireless modem.

27. A carrier signal modulated with an information signal for communicating between two wireless devices, the information signal comprising a header portion and a data portion, the header portion comprising a modulation identity portion comprising information identifying a modulation type of a plurality of modulation types utilized to modulate the data portion of the information signal.

28. The carrier signal modulated with the information signal for communicating between two wireless devices of Claim 27 wherein the header portion further comprises timing and synchronization for the particular information signal.

5

29. The carrier signal modulated with the information signal for communicating between two wireless devices of Claim 27 wherein the data portion comprises a in-phase pilot signal that is capable of being utilized to determine the frequency of the carrier signal.

30. The carrier signal modulated with the information signal for communicating between two wireless devices of Claim 27 wherein the data portion comprises a fixed data pattern and wherein the information signal is utilized as a training signal.

31. The carrier signal modulated with the information signal for communicating between two wireless devices of Claim 27 wherein the header portion is modulated utilizing a first type of modulation and the data portion is modulated utilizing a second type of modulation different than the first type of modulation.

FOIA b 7 - DATED 03/14/2015 BY SP4 BTB/STP

20



32. The method according to Claim 27, wherein said computer instruction are compiled computer instructions stored as an executable program on said computer readable media.

5 *R 1-126* 33. The method according to Claim 20, wherein said method is embodied in a set of computer readable instructions stored in an electronic signal.

704060-03470350